



1810 AUTO DIALER TELEPHONE INTERCOM SYSTEM

www.leedan.com info@leedan.com Toll-Free: 800-231-1414



flush mount



surface mount



led lit
directory display



built-in display
indicates door/gate has
been opened



dtmf tone output
allows these systems to be used
with PBX, KSU and telephone
systems with auto-attendants



two mounts
surface and flush are available

- Provides both resident and visitor access control into apartment buildings, gated communities, condominiums, office buildings, factories and industrial sites
- Visitors use the 1810 to communicate with a resident, who can then grant or deny them access from their touch-tone telephone
- Provides service for up to 1000 residents
- Programmable directory codes can be set from 1 to 4 digits
- Built in lighted paper directory




FEATURES

ACCESS CONTROL SOLUTIONS



The model 1810 is an ideal telephone entry system that is suited for a wide variety of applications. The built-in lighted directory makes it a complete all-in-one compact unit and it is easy for managers to update by using a word processing program. Visitors are easily identified by voice communication and can be granted or denied access directly from a touch-tone telephone.

www.leedan.com info@leedan.com Toll-Free: 800-231-1414



1810 Surface
11.25" W x 13" H x 4.75" D
28.5cm W x 33cm H x 12cm D

1810 Flush
12" W x 13.25" H x 3" D
30.4cm W x 33.65cm H x 7.62cm D

1810 Specs

Communication

True full duplex
Hands free
Optional handset available (ADA compliant) on surface mount units only

Display & Mounting Styles

Surface or flush mount
Display for programming assistance and shows 'open' when access is granted
Built-in LED lighted paper display

Capacity

1000 phone numbers, 10 area codes
4 digit entry codes same as system memory
5 digit entry codes = 6

Door/Gate Control

Two relays allow for control of both a vehicular gate and a pedestrian gate

Programming Methods

System keypad
Touch-tone telephone

Advanced Features

Programmable directory codes can be set from 1 to 4 digits in length
10 & 11 digit dialing capability
LCD Programming display
Built in clock/calendar
Time clock has its own backup power source
Entry code time zones
Four hold-open time zones
Flash entry codes
DTMF tone output allows for use with KSU, PBX and systems with an auto-attendant
Two special inputs can be programmed for relay activation or dial-out function
Time zone restrictions on selected entry codes
Built-in postal lock provision

Options

Stainless Steel housing available on surface mount styles only
Gold-plated faceplate available on flush mount style only
Fluorescent light kit
Heater kit - recommended when temperatures routinely fall below 10°F (-12°C)
Camera Ready:
Optional B&W or Color CCTV camera*
*may require additional CCTV equipment

Operating Temp

10°F to 145°F
-12°C to 62°C
Optional heater kit available for colder climates

Electrical Requirements

16 VAC, 20 VA System power (250 ma)
U.L. listed power transformer provided
Ringer equivalence: 0.0A Jack Type: RJ11C or W

Safety Standards

FCC (US) DUF6VT-12874-OT-0
DOC (CAN) 1736 4507 A
Complies with UL 294
ETL Listed

Shipping Weight

Approximately 20-25 lbs (9-11.3 kg)

Warranty

2 year limited factory warranty

Distributed by:

DOORKING®, INC.

© 2008 All Rights Reserved. Product specifications may change without notice. Rev. 8/08

MEMBER:

