

ANNUNCIATOR CONTROL UNIT

APPLICATION

The TekTone® PK-2019 (PK2019) Annunciator Control Unit is a general purpose annunciator control unit that is used with the CM-800 Emergency Call System and the DS-100 Door Sentry System.

The PK-2019 provides tone signal, tone silencing, tone-silenced indication, auxiliary signal relay, and 24 VDC for accessory device operation.

FEATURES

- Low-voltage operation
- Rugged extruded aluminum case.
- Positive screw terminals

SPECIFICATIONS

Dimensions: 5.0" High (127 mm)
Width: 2.375" (61 mm)
Depth: 2.25" (58 mm)

Construction: Quality electronic components mounted on a PC board encased in a rugged extruded aluminum housing.

Connections: Screw terminals

Power Required: 16 VAC 30 VA max.

Output Current: 1 Amp. maximum

Tone Speaker: 45 ohms (up to 3 in parallel)

Tone-Off Lamp: .04 Amp. (up to 3 in parallel)

REQUIRED COMPONENTS

PS-30A UL Transformer, 16VAC, 30VA
CM-800 Series Annunciator Panel
-or-
DS-100 Series Speaker Panel



PK-2019

ARCHITECTS' AND ENGINEERS' SPECIFICATIONS

The annunciator control unit shall be TekTone® PK-2019 or approved equivalent as supplied by LEE DAN®. It shall be used with the CM-800 Emergency Call System and/or the DS-100 Door Sentry System.

The PK-2019 shall be capable of generating either a steady or intermittent alarm tone.

Screw terminals shall be provided for connections. The control unit shall be of rugged construction and modular integrated circuit design.