Innovations in Communications™ since 1955



# **AREA-OF-RESCUE REMOTE CALL STATIONS**

## APPLICATION

Used with TekTone<sup>®</sup>'s Tek-SAFE<sup>®</sup> NC150R Area of Rescue Assistance System, IR150SS-series Remote Call Stations provide efficient communication between areas of rescue assistance (in protected stairwells) and the building lobby. IR150SS-series Remote Call Stations are located in areas of rescue assistance to provide two-way hands-free communication to a central location from which help may be summoned. Calls are placed by pressing a large, red momentary push button. Solid state indicators on the panel indicate when a call has been placed and when the intercom is in use.

• **IR150SS** (IR-150SS) is a flush mount station with a large mushroom style push button. Use flush mount housing OH-600.

• **IR150SS/S** (IR-150SS/S) is a surface mount station with a large mushroom-style push button.

• **IR150SSF** (IR-150SSF) is a flush mount station with a large low profile push button. Use flush mount housing OH-600.

• **IR150SS/SF** (IR-150SS/SF) is a surface mount station with a large low-profile push button.

### **FEATURES**

- Push button calling via large red mushroom-style or low-profile button
- Call-placed indicator Audio-on indicator
- Sensitive speaker/microphone Cancel Button
- Attractive and durable stainless steel panel
- Weather resistant when properly installed



IR150SS (IR-150SS) Flush <u>Mushroom Button Type</u> Not Shown: Surface Mount IR150SS/S (IR-150SS/S)



IR150SSF (IR-150SF) Flush <u>Recessed Button Type</u> Not Shown: Surface Mount IR150SS/SF (IR-150SS/SF)

### **REQUIRED COMPONENTS**

Tek-Safe<sup>TM</sup> Area-of-Rescue System including NC-150R Master Annunciator & Related Components

#### **SPECIFICATIONS**

*Dimensions:* Height 5" (127 mm) Width 11.1" (282 mm) Depth 1.75" (45 mm)

*Connections:* 6 Screw terminal block

Construction: Durable Stainless Steel Panel Finish: Brushed Stainless Steel IR-150SS/S + IR-150SS/SF (NO housing: Surface Mount)

Housing: IR-150SS + IR-150SSF use OH600 (OH-600)

Projects: IR-150SS: 1.5" (38 mm) above mounting surface

IR-150SS/S: 3.5" (89 mm) above mounting surface

Speaker: 3.5" Mylar Screws: Phillips

800-231-1414 • 631-231-1414 155 Adams Avenue • Hauppauge, NY 11788-3699 Fax 631-231-1498 • www.*LEEDAN*.com

INTERCOMS • NURSE-CALL • ANNUNCIATORS DIRECTORIES • MAILBOXES • WIRE & CABLE With continuous product improvement, specifications are subject to change without notice.

©2013 LEE DAN® Communications, Inc.